PC2100

Automatic 12V 21A 6 Stage Battery Charger

A powerful charger offering a comprehensive 6 stage charge ideal for a wide range of battery sizes.





Suitable for a wide range of different size batteries



Adjusts the charging profile to suit calcium batteries



Revitalises tired batteries, increasing battery life and performance*



Optional mounting wings for permanent installation



Spark free and polarity protected

SPECIFICATIONS

PRODUCT DETAILS		L.E.D CHARGE INDICATION			
PART NO.	PC2100	BLUE LIGHT ON	Bulk and absorption charging		
TYPE	6 stage	GREEN LIGHT ON	Fully charged and maintaining,		
INPUT	240VAC, 50Hz, 600W		no need to turn off		
OUTPUT	12V	AMBER LIGHT ON	Rejuvenation process occurring		
OUTPUT CURRENT	2, 6, 12, 21A	• RED LIGHT ON	Indicates faulty battery		
MINIMUM START VOLTAGE	3.0V	BATTERY CHARGE TIMES			
BACK DRAIN	1mA	PC2100	VOLTAGE	BATTERY SIZE	CHARGE TIME
APPROVALS	Electrical Safety, EMC	AUTOMOTIVE	12V	80-2500CCA	7–24 hrs
		MARINE	12V	110-3500MCA	7–24 hrs
		DEEP CYCLE	12V	14–420Ah	7-24 hrs

APPLICATIONS

Ideal Battery Types











^{*} Subject to battery condition











