



# Braille Battery™ Advanced AGM™ B2015 Lightweight Battery **Lighter. Stronger. Faster**



- Easy Install: Usable for all Group Sizes, Drop In Replacement
- Faster: Up to 40% Lighter, Less HP Loss
- Safer: Sealed Safe Design, Non-Spilling
- Efficient: Stable Voltage Output, Less Stress on Alternator
- Greener: Constructed from Premium Recycled Materials
- Reliable: Individually Certified, Racing Warranty, Made in USA

## PHYSICAL SPECS

Replacement Group:	Usable for all Group Sizes
Length:	6.8" / 172.7 mm
Width:	3.4" / 86.4 mm
Height:	6.1" / 154.9 mm
Minimum Weight (lbs):	15 lbs / 6.75 kg
Terminals:	Vertical or Horizontal
Auto Posts:	TrueTorque SAE Auto Posts
Polarity:	Left Positive
Recommended Mounts:	#2018, 211, 6186, 6188

## PERFORMANCE

Voltage Class:	12 volts
Full Charge Range:	13.8 volts
Max Amps:	2500
Pulse Cranking Amps:	1067
Cranking Amps @ 32F:	574
Cranking Amps @ 0F:	426
Nominal Capacity:	21 AH
Internal Resistance (ohms):	< 4.5 milliohms (.0045ohms)
Life Cycle @ 10% DOD:	3100 cycles



*Braille B2015 Model Shown w/ TrueTorque™ Terminals attached*

## CHARGING INFORMATION

Alternator:	Automotive, Marine and Cycle Compatible
Battery charger:	Braille Model 1232 – 2 amp charger
Rapid Recharge:	Yes, 10-20 amp/hr electronically controlled
Maximum Charge Voltage @70F:	40 amp/hr
Recommended Charge Voltage:	14.45 – 14.75 Volts

## WARRANTY

Warranty: 2 year pro-rated Warranty / 1 year free replacement



Actual performance may vary. Pricing, specifications and features calculated as of 5/16, subject to change without notice. For latest information, contact Braille directly.  
Braille Battery, Sarasota, FL USA    Ph: 941-312-5047    Fax: 941-870-3381    Email: sales@braillebattery.com    Web: www.braillebattery.com  
Copyright Braille Battery, Inc 2014    Braille AAGM Lightweight Spec Data 1.17