



Braille Battery™ 2016 MICRO-LiTE™ Lithium Technology

Lighter. Stronger. Faster.

Part Number: ML14C
Model Name: Braille MICRO-LiTE Lithium Technology Racing Battery



- Easy Install: Direct Drop In Replacements
- Faster: Only 4.5 Pounds with the Power you Need
- Safer: Sealed Safe Design, Low Voltage Protection
- Efficient: Stable Voltage Output, Less Stress on Alternator
- Greener: Modular Design For Longer Life
- Reliable: Longer Life backed by Racing Warranty

PHYSICAL SPECS

Length: 5.8" / 147.3 mm
 Width: 3.4" / 86.4 mm
 Height: 5.75" / 146.05mm
 Weight: 4.5 lbs / 2.03 kg
 BCI Group: 14 - Same Size as B14115C Battery
 Polarity: Left Positive – (Right Custom)
 Post Type: Stainless Steel Female Threads;
 SAE Automotive Posts Included
 – Variable Mounting

Recommended Mount: Braille 1418 Horizontal Aluminum,
 Braille 211 Vertical Aluminum

PERFORMANCE

Voltage: 12 volts
 Full Charge Voltage Range: 13.8 volts
 PCA 5 sec @ 80F*: 952
 Lead-Acid Equivalent Capacity: 42 Lithium AH (LAH)
 Nominal Capacity (C/20 rate)*: 14 AH
 Life Cycle @ 10% DOD: Up to 5000 cycles

CHARGING INFORMATION

Alternator: Automotive & Marine Compatible
 Battery charger: Model# 12310L &12325L compatible
 Rapid Recharge: 25 AH electronically controlled
 Recommended Charge Voltage: 14.4 - 14.8 Volts
 Do Not Exceed Charge Voltage: 16 Volts

WARRANTY

Warranty: 1 Year Free repair/replacement. See warranty terms and conditions.



*ML14C Model Shown
with TrueTorque™ Terminals
attached*

* Performance specifications denote maximum lead-acid equivalents. Actual performance may vary. Pricing, specifications and features current as of 3/16, subject to change without notice. For latest information, contact Braille directly.