



Braille Battery™ 2016 MICRO-LiTE™ Lithium Technology

Lighter. Stronger. Faster.

Part Number: ML20C
Model Name: Braille MICRO-LiTE Lithium Technology Racing Battery



- Easy Install: Direct Drop In Replacements
- Faster: Only 6.1 Pounds with the Power You Need
- Safer: Sealed Safe Design, Low Voltage Protection
- Efficient: Stable Voltage Output, Less Stress on Alternator
- Greener: Modular Design For Longer Life
- Reliable: Longer Life Backed by Racing Warranty

PHYSICAL SPECS

Length: 6.8" / 173 mm
 Width: 3.4" / 86.4 mm
 Height: 6" / 152.4 mm
 Weight: 6.1 lbs / 2.75 kg
 BCI Group: 20 - Same Size as B2015C Battery
 Polarity: Right Positive – (Left Custom)
 Post Type: Stainless Steel Female Threads;
 SAE Automotive Posts Included
 – Variable Mounting
 Recommended Mount: Braille 2018 Horizontal Aluminum,
 Braille 211 Vertical Aluminum

PERFORMANCE

Voltage: 12 volts
 Full Charge Voltage Range: 13.8 volts
 PCA 5 sec @ 80F*: 1325
 Lead-Acid Equivalent Capacity: 48 Lithium AH (LAH)
 Nominal Capacity (C/20 rate)*: 16 AH
 Life Cycle @ 10% DOD: Up to 5000 cycles



ML20C Model Shown
With TrueTorque™ Terminals
Attached

CHARGING INFORMATION

Alternator: Automotive & Marine Compatible
 Battery charger: Model# 12310L & 12325L compatible
 Rapid Recharge: 25 AH electronically controlled
 Recommended Charge Voltage: 14.4 - 14.8 Volts
 Do Not Exceed Charge Voltage: 16 Volts

WARRANTY

Warranty: 1 Year Free repair/replacement. See warranty terms and conditions.



braille
BATTERY
 LIGHTER • STRONGER • FASTER
 a GRAFOID company

* Performance specifications denote maximum lead-acid equivalents. Actual performance may vary. Pricing, specifications and features current as of 3/16, subject to change without notice. For latest information, contact Braille directly.